

GSM/DCS/WCDMA 六工器调试指标(CB-900-1800-2100-30-01)

序号	指标项目	技术指标					
		GSM		DCS		WCDMA	
1	频段	884.5-915.5MHz	924.5-960.5MHz	1709-1786MHz	1804-1881MHz	1919-1981MHz	2109-2171MHz
2	带内插损	≤1.9dB	≤1.9dB	≤1.9dB	≤1.9dB	≤1.7dB	≤1.3dB
3	带内纹波	≤1.5dB	≤1.5dB	≤1.5dB	≤1.5dB	≤1.0dB	≤0.5dB
4	带外抑制	≥45dB@920MHz (极限温度≥36) ≥92dB@924.5-2171MHz	≥45dB@920MHz (极限温度≥36) ≥92dB@884.5-95.5MHz ≥93dB@1709-2171MHz	≥43dB@1795MHz (极限温度≥36) ≥92dB@884-961MHz ≥92dB@1709-2171MHz	≥43dB@1795MHz (极限温度≥36) ≥43dB@1900MHz ≥93dB@884-1786MHz ≥92dB@1919-2171MHz	≥45dB@1900MHz ≥50dB@2045MHz ≥93dB@884-1881MHz ≥93dB@2109-2171MHz	≥50dB@2045MHz ≥93dB@884-1981MHz
5	隔离度	≥92dB					
6	端口回波	≥21dB					
7	功率容量	≤30W(CW)					
8	工作温度	-10℃~+50℃					
9	接头	ANT-NK/ 其于SMA-KF, 50Ω					
10	尺寸	170*170*90mm (长*宽*厚)					
11	外观颜色	黑色					



