

CDMA-DCS-WCDMA 六工器规格书
CDMA-DCS-WCDMA 6Way Multiplexer Specification
(Model: MX-825-2170-20-06)

项目 Item	技术指标 Technical					
	CDMA		DCS		WCDMA	
	C-RX	C-TX	D-RX	D-TX	W-RX	W-TX
端口名称 PortName						
频率 Frequency	825-845MHz	870-890 MHz	1710-1785 MHz	1805-1880 MHz	1920-1980 MHz	2110-2170 MHz
插损 Insertion Loss	≤1.5dB	≤1.5dB	≤1.8dB	≤1.8dB	≤1.5dB	≤1.5dB
带内波动 Ripple	≤1.5dB	≤1.5dB	≤1.5dB	≤1.5dB	≤1.2dB	≤0.8dB
带外抑制 Rejection	≥90dB@837.5 MHz ≥80dB@870-2170 MHz	≥80dB@825-845 MHz ≥60dB@857.5 MHz ≥90dB@1710-2170 MHz	≥30dB@825-890 MHz ≥55dB@1795 MHz ≥80dB@1805-2170 MHz	≥80dB@825-890 MHz ≥78dB@1710-1785 MHz ≥55dB@1795 MHz ≥50dB@1900 MHz ≥80dB@1920-2170 MHz	≥80dB@825-890 MHz ≥80dB@1710-1880 MHz ≥55dB@1900 MHz ≥60dB@2045 MHz ≥80dB@2110-2170 MHz	≥80dB@825-890 MHz ≥80dB@1710-1920 MHz ≥60dB@2045 MHz
驻波比 VSWR	≤1.3					
隔离度 Isolation	≥70dB					
功率容量 Power	≤20W					
特性阻抗 Impedance	50Ω					
接头 Connector Type	ANT/N-KFD/SMA-Female					
温度 Temperature	-10~+50℃					
喷漆颜色 Colour	华为灰					



CDMA/DCS/WCDMA六工器
C-RX:825-845 C-TX:870-890
D-RX:1710-1785 D-TX:1805-1880
W-RX:1920-1980 W-TX:2110-2170
SN:

